

Grip It, Rip It, and Get The Job Done!™

3 lbs

4 lbs

6 lbs

2.5 lbs

2.75 lbs

2 lbs



Strikeforce[™] **Sledge Hammers**

Hammer, Blacksmith's Sledge

with Fiberglass Handle





No.	H g	l mm	∆'∆ g	H lbs.	l inch	۵۵ lbs.
H-142FG	800	280	955	2.00	11	2.10
H-14FG	800	350	1000	2.00	14	2.20
H-152FG	1000	280	1180	2.50	11	2.60
H-15FG	1000	350	1180	2.50	14	2.60
H-162FG	1250	280	1360	2.75	11	3.00
H-16FG	1250	350	1450	2.75	14	3.20
H-172FG	1500	280	1495	3.00	11	3.30
H-17FG	1500	350	1540	3.00	14	3.40
H-182FG	2000	280	1995	4.00	11	4.40
H-18FG	2000	350	2040	4.00	14	4.50
H-702FG	3000	380	3085	6.00	15	6.80



No.	H g	l mm	Δ [†] Δ g	H Ibs.	l inch	۵۵ lbs.
H-69FG	1500	350	1540	3.00	14	3.40
H-70FG	3000	840	3040	6.00	33	6.70
H-71FG	3500	840	4035	8.00	33	8.90
H-712FG	4000	840	4080	9.00	33	9.00
H-72FG	4500	840	4715	10.00	33	10.40
H-722FG	5000	840	5985	11.00	33	13.20
H-724FG	5500	840	6375	12.00	33	14.05
H-726FG	6000	840	6895	13.00	33	15.20
H-73FG	7000	840	7030	16.00	33	15.50
H-74FG	8000	840	8575	18.00	33	18.90
H-76FG	10000	840	10750	22.00	33	23.70

Power in the Clutch!™

Grip It, Rip It, and Get The Job Done!™

Non-Sparking

OSHA, NFPA, MSHA and other Standards Developing Organizations recommend and require the use of Non-Sparking Tools where flammable liquids, vapors, dust or residue are present. An investment in AMPCO Non-Sparking Tools today may help prevent dangerous and costly fires tomorrow!

Non-Magnetic

AMPCO Non-Magnetic Hand Tools prevent accidents and protect property in medical, military and electronics manufacturing locations. They have been independently tested and found to pose no risk in MRI environments, conforming to ASTM F2503 and also meeting the requirements established by ASTM A342. They are ideal for use near highly sensitive magnetic equipment and in clean room environments.

Corrosion Resistant

Salt water, chemicals and acids take a toll on standard hand tools. Unlike steel tools, AMPCO Hand Tools provide durability even in the most severe corrosive environments.

Quality Tools for a Safe Workplace — Since 1922®

AMPCO SAFETY TOOLS.COM

Tel.: 972-276-6181

Toll Free: 1-800-580-9835

Fax: 972-276-5815

Sales@AmpcoSafetyTools.com